




1. RECOMMENDED MOUNTING HOLE:  $\varnothing 0.89 \pm 0.08 [ .035 \pm .003 ]$ .
2. POINT OF MEASUREMENT FOR PLATING THICKNESS.
3. HOUSING: GLASS FILLED NYLON. COLOR – BLACK.  
POSTS: PHOS. BRONZE
4. 0.00076 [ .000030 ] GOLD IN CONTACT AREA, GOLD FLASH ON  
REMAINDER OF POSTS, ALL OVER 0.00127 [ .000050 ] NICKEL.
5. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 31-MAR-97 E. BRANDBERG		tyco Tyco Electronics Corporation Harrisburg, Pa 17105-3608							
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME							
		S. SHUEY 31-MAR-97		HEADER ASSEMBLY, MOD II, 2.54[.100] CL, RIGHT ANGLE, 0.64[.025] SQUARE POST, SINGLE ROW							
		APVD S. SHUEY 31-MAR-97									
		PRODUCT SPEC									
		APPLICATION SPEC									
0 PLC ± - 1 PLC ± - 2 PLC ± 0.13[.005] 3 PLC ± - 4 PLC ± - ANGLES ± ± -		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO					
MATERIAL		FINISH		WEIGHT		A2		00779	C-87232	-	
				CUSTOMER DRAWING		SCALE	5:1	SHEET	1 of 1	REV	H1