


PM series Extremely Low Impedance, High Reliability




- High reliability withstanding 5000 hour load life at +105°C (3000/2000 hours for smaller case sizes as specified below).
- Capacitance ranges available based on the numerical values in E12 series under JIS.
- Adapted to the RoHS directive (2002/95/EC).

Specifications

| Item | Performance Characteristics | | | | | | | | | | | | |
|------------------------------|---|---|----------|------|---------|--------|--|----------|-----------|-----------|--------------------|---|--|
| Category Temperature Range | -55 ~ +105°C (6.3 ~ 100V), -40 ~ +105°C (160 ~ 400V), -25 ~ +105°C (450V) | | | | | | | | | | | | |
| Rated Voltage Range | 6.3 ~ 450V | | | | | | | | | | | | |
| Rated Capacitance Range | 0.47 ~ 15000μF | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% at 120Hz, 20°C | | | | | | | | | | | | |
| Leakage Current | Rated Voltage (V) | 6.3 ~ 100 | | | | | 160 ~ 450 | | | | | | |
| | Leakage current | After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4 (μA), whichever is greater. | | | | | CV ≤ 1000 : I = 0.1CV+40 (μA) max. (1 minute's) CV > 1000 : I = 0.04CV+100 (μA) max. (1 minute's) | | | | | | |
| tan δ | For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF. Measurement frequency : 120Hz, Temperature : 20°C | | | | | | | | | | | | |
| | Rated Voltage (V) | 6.3 | 10 | 16 | 25 | 35 | 50 | 63 ~ 100 | 160 ~ 350 | 400 ~ 450 | | | |
| | tan δ (MAX.) | 0.22 | 0.19 | 0.16 | 0.14 | 0.12 | 0.10 | 0.08 | 0.20 | 0.25 | | | |
| Stability at Low Temperature | Rated voltage (V) | | 6.3 - 10 | 16 | 25 - 35 | 50~100 | 160~200 | 250 | 315~350 | 400 | 450 | 120Hz | |
| | Impedance ratio (MAX.) | Z-25°C / Z+20°C | — | — | — | — | — | — | — | — | 15 | | |
| | | Z-40°C / Z+20°C | — | — | — | — | 4 | 6 | 8 | 10 | — | | |
| | | Z-55°C / Z+20°C | 4 | 3 | 3 | 2 | — | — | — | — | — | | |
| Endurance | After an application of D.C. bias voltage plus the rated ripple current for 5000 hours (2000 hours for D = 5 and 6.3, 3000 hours for D=8) at 105°C the peak voltage shall not exceed the rated D.C. voltage, capacitors meet the characteristic requirements listed at right. | | | | | | | | | | | | |
| | | | | | | | | | | | Capacitance change | Within ±20% of initial value | |
| | | | | | | | | | | | tan δ | 200% or less of initial specified value | |
| | | | | | | | | | | | Leakage current | Initial specified value or less | |
| Shelf Life | After storing the capacitors under no load at 105°C for 1000 hours, and after performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they will meet the characteristic requirements listed at right. | | | | | | | | | | | | |
| | | | | | | | | | | | Capacitance change | Within ±20% of initial value | |
| | | | | | | | | | | | tan δ | 150% or less of initial specified value | |
| | | | | | | | | | | | Leakage current | Initial specified value or less | |
| Marking | Printed with white color letter on dark brown sleeve. | | | | | | | | | | | | |

Radial Lead Type




| | |
|---|---------------|
| α | (φD < 10) 1.5 |
| | (φD ≥ 10) 2.0 |

| | φD | 5 | 6.3 | 8 | 10 | 12.5 | 16 | 18 |
|----|-----|-----|-----|-----|-----|------|-----|----|
| P | 2.0 | 2.5 | 3.5 | 5.0 | 5.0 | 7.5 | 7.5 | |
| φd | 0.5 | 0.5 | 0.6 | 0.6 | 0.6 | 0.8 | 0.8 | |

※ In case L > 25 for the φ12.5 dia. unit, lead dia. φd = 0.8mm.

- Please refer to page 21 about the end seal configuration.


Type numbering system (Example : 25V 470μF)



※ Configuration

| φ D | Pb-free leadwire Pb-free PET sleeve |
|-----------|--|
| 5 | DD |
| 6.3 | ED |
| 8 · 10 | PD |
| 12.5 ~ 18 | HD |

Frequency coefficient of rated ripple current



Please refer to page 21, 22, 23 about the formed or taped product spec.
Please refer to page 3 for the minimum order quantity.

- Dimension table in next page.

■ Dimensions

φD×L (mm)

| Cap.(μF) | V(Code) Size code | 6.3 (0J) | | 10 (1A) | | 16 (1C) | | 25 (1E) | | 35 (1V) | |
|----------|----------------------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|
| | | — | 6 | — | 6 | — | 6 | — | 6 | — | 6 |
| 22 | 220 | | | | | | | | | 5 × 11 | |
| 27 | 270 | | | | | | | | | 5 × 11 | |
| 33 | 330 | | | | | | | 5 × 11 | | 6.3 × 11 | |
| 39 | 390 | | | | | | | 5 × 11 | | 6.3 × 11 | |
| 47 | 470 | | | | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | |
| 56 | 560 | | | | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | |
| 68 | 680 | | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | |
| 82 | 820 | | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | |
| 100 | 101 | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 11.5 | |
| 120 | 121 | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 15 | 10 × 12.5 |
| 150 | 151 | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 11.5 | | 8 × 15 | 10 × 12.5 |
| 180 | 181 | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 |
| 220 | 221 | 6.3 × 11 | | 6.3 × 15 | | 8 × 11.5 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 |
| 270 | 271 | 6.3 × 15 | | 6.3 × 15 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 |
| 330 | 331 | 6.3 × 15 | | 8 × 11.5 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 |
| 390 | 391 | 8 × 11.5 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 |
| 470 | 471 | 8 × 15 | 10 × 12.5 | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 |
| 560 | 561 | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 | 12.5 × 20 | 16 × 15 |
| 680 | 681 | 8 × 20 | 10 × 15 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 |
| 820 | 821 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 | 12.5 × 20 | 16 × 15 | 12.5 × 25 | 18 × 15 |
| 1000 | 102 | 10 × 20 | 12.5 × 15 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 31.5 | 16 × 20 |
| 1200 | 122 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 | 12.5 × 20 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 35.5 | 16 × 25 |
| 1500 | 152 | 10 × 25 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 |
| 1800 | 182 | 10 × 31.5 | 16 × 15 | 12.5 × 20 | 16 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 35.5 | 16 × 25 | 16 × 31.5 | 18 × 25 |
| 2200 | 222 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 31.5 |
| 2700 | 272 | 12.5 × 25 | 18 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 35.5 | 16 × 25 | 16 × 31.5 | 18 × 25 | 16 × 40 | 18 × 35.5 |
| 3300 | 332 | 12.5 × 25 | 18 × 15 | 12.5 × 35.5 | 16 × 20 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 31.5 | 18 × 40 | |
| 3900 | 392 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 | 16 × 31.5 | 18 × 25 | 16 × 40 | 18 × 35.5 | | |
| 4700 | 472 | 12.5 × 35.5 | 18 × 20 | 16 × 31.5 | 18 × 25 | 16 × 35.5 | 18 × 31.5 | 18 × 40 | | | |
| 5600 | 562 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 25 | 16 × 40 | 18 × 35.5 | | | | |
| 6800 | 682 | 16 × 31.5 | 18 × 25 | 16 × 35.5 | 18 × 31.5 | 18 × 35.5 | | | | | |
| 8200 | 822 | 16 × 35.5 | 18 × 31.5 | 16 × 40 | 18 × 35.5 | 18 × 40 | | | | | |
| 10000 | 103 | 16 × 40 | 18 × 31.5 | 18 × 40 | | | | | | | |
| 12000 | 123 | 18 × 35.5 | | | | | | | | | |
| 15000 | 153 | 18 × 40 | | | | | | | | | |

| Cap.(μF) | V(Code) Size code | 50 (1H) | | 63 (1J) | | 80 (1K) | | 100 (2A) | |
|----------|----------------------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|
| | | — | 6 | — | 6 | — | 6 | — | 6 |
| 0.47 | R47 | 5 × 11 | | | | | | 5 × 11 | |
| 0.68 | R68 | 5 × 11 | | | | | | 5 × 11 | |
| 1 | 010 | 5 × 11 | | | | | | 5 × 11 | |
| 1.5 | 1R5 | 5 × 11 | | | | | | 5 × 11 | |
| 2.2 | 2R2 | 5 × 11 | | | | | | 5 × 11 | |
| 3.3 | 3R3 | 5 × 11 | | | | | | 5 × 11 | |
| 4.7 | 4R7 | 5 × 11 | | | | 5 × 11 | | 6.3 × 11 | |
| 6.8 | 6R8 | 5 × 11 | | | | 5 × 11 | | 6.3 × 11 | |
| 10 | 100 | 5 × 11 | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | |
| 12 | 120 | 5 × 11 | | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | |
| 15 | 150 | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | |
| 18 | 180 | 5 × 11 | | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | |
| 22 | 220 | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 11.5 | |
| 27 | 270 | 6.3 × 11 | | 6.3 × 11 | | 6.3 × 15 | | 8 × 15 | 10 × 12.5 |
| 33 | 330 | 6.3 × 11 | | 6.3 × 15 | | 8 × 11.5 | | 8 × 15 | 10 × 12.5 |
| 39 | 390 | 6.3 × 11 | | 6.3 × 15 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 |
| 47 | 470 | 6.3 × 15 | | 8 × 11.5 | | 8 × 15 | 10 × 12.5 | 10 × 20 | 12.5 × 15 |
| 56 | 560 | 6.3 × 15 | | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 |
| 68 | 680 | 8 × 11.5 | | 8 × 15 | 10 × 12.5 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 |
| 82 | 820 | 8 × 15 | 10 × 12.5 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 |
| 100 | 101 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 | 10 × 31.5 | 16 × 15 |
| 120 | 121 | 8 × 20 | 10 × 15 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 16 × 15 |
| 150 | 151 | 10 × 20 | 12.5 × 15 | 10 × 25 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 |
| 180 | 181 | 10 × 20 | 12.5 × 15 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 16 × 15 | 12.5 × 31.5 | 16 × 20 |
| 220 | 221 | 10 × 25 | 12.5 × 15 | 12.5 × 20 | 16 × 15 | 12.5 × 31.5 | 18 × 15 | 12.5 × 35.5 | 16 × 25 |
| 270 | 271 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 |
| 330 | 331 | 10 × 31.5 | 16 × 15 | 12.5 × 25 | 18 × 15 | 12.5 × 35.5 | 16 × 25 | 16 × 31.5 | 18 × 25 |
| 390 | 391 | 12.5 × 25 | 16 × 15 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 31.5 |
| 470 | 471 | 12.5 × 25 | 18 × 15 | 12.5 × 35.5 | 16 × 25 | 16 × 31.5 | 18 × 25 | 16 × 40 | 18 × 35.5 |
| 560 | 561 | 12.5 × 31.5 | 16 × 20 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 31.5 | 18 × 35.5 | |
| 680 | 681 | 12.5 × 35.5 | 16 × 20 | 16 × 31.5 | 18 × 25 | 16 × 40 | 18 × 31.5 | 18 × 40 | |
| 820 | 821 | 12.5 × 40 | 18 × 20 | 16 × 35.5 | 18 × 31.5 | 18 × 35.5 | | | |
| 1000 | 102 | 16 × 31.5 | 18 × 25 | 16 × 40 | 18 × 35.5 | 18 × 40 | | | |
| 1200 | 122 | 16 × 35.5 | 18 × 31.5 | 18 × 40 | | | | | |
| 1500 | 152 | 16 × 40 | 18 × 31.5 | | | | | | |
| 1800 | 182 | 18 × 35.5 | | | | | | | |
| 2200 | 222 | 18 × 40 | | | | | | | |

※In case of low profile type, [6] will be put at 12th digit of type numbering system.

Dimension table for 160 ~ 450V products are shown in 122 page.

■ Standard ratings

| <div> <div>V(Code)</div> <div>Size code</div> <div>Item</div> <div>Cap.(μF)</div> <div>Code</div> </div> | | 6.3 (0J) | | | | | | | | | |
|--|-----|-----------------------------|--------------------|----------------|---------------------------|---------------|-----------------------------|--------------------|----------------|---------------------------|---------------|
| | | — | | | | | 6 | | | | |
| | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | |
| | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz |
| 100 | 101 | 5 × 11 | 0.85 | 1.70 | 150 | 99 | | | | | |
| 120 | 121 | 5 × 11 | 0.65 | 1.30 | 175 | 115 | | | | | |
| 150 | 151 | 6.3 × 11 | 0.49 | 0.98 | 225 | 155 | | | | | |
| 180 | 181 | 6.3 × 11 | 0.39 | 0.78 | 250 | 175 | | | | | |
| 220 | 221 | 6.3 × 11 | 0.30 | 0.60 | 285 | 205 | | | | | |
| 270 | 271 | 6.3 × 15 | 0.24 | 0.48 | 370 | 275 | | | | | |
| 330 | 331 | 6.3 × 15 | 0.20 | 0.40 | 405 | 310 | | | | | |
| 390 | 391 | 8 × 11.5 | 0.17 | 0.34 | 445 | 345 | | | | | |
| 470 | 471 | 8 × 15 | 0.14 | 0.28 | 550 | 435 | 10 × 12.5 | 0.14 | 0.28 | 635 | 455 |
| 560 | 561 | 8 × 15 | 0.12 | 0.24 | 595 | 480 | 10 × 12.5 | 0.13 | 0.26 | 600 | 485 |
| 680 | 681 | 8 × 20 | 0.10 | 0.20 | 730 | 605 | 10 × 15 | 0.11 | 0.22 | 825 | 580 |
| 820 | 821 | 8 × 20 | 0.085 | 0.17 | 795 | 670 | 10 × 15 | 0.095 | 0.19 | 825 | 635 |
| 1000 | 102 | 10 × 20 | 0.075 | 0.15 | 950 | 820 | 12.5 × 15 | 0.085 | 0.17 | 890 | 765 |
| 1200 | 122 | 10 × 20 | 0.065 | 0.13 | 1060 | 895 | 12.5 × 15 | 0.075 | 0.15 | 950 | 835 |
| 1500 | 152 | 10 × 25 | 0.055 | 0.11 | 1260 | 1090 | 12.5 × 15 | 0.065 | 0.13 | 1020 | 915 |
| 1800 | 182 | 10 × 31.5 | 0.050 | 0.10 | 1370 | 1230 | 16 × 15 | 0.055 | 0.11 | 1270 | 1140 |
| 2200 | 222 | 10 × 31.5 | 0.043 | 0.086 | 1470 | 1320 | 16 × 15 | 0.049 | 0.098 | 1340 | 1200 |
| 2700 | 272 | 12.5 × 25 | 0.038 | 0.076 | 1700 | 1430 | 18 × 15 | 0.044 | 0.088 | 1500 | 1350 |
| 3300 | 332 | 12.5 × 25 | 0.034 | 0.068 | 1710 | 1530 | 18 × 15 | 0.039 | 0.078 | 1600 | 1440 |
| 3900 | 392 | 12.5 × 31.5 | 0.031 | 0.062 | 1980 | 1710 | 16 × 20 | 0.036 | 0.072 | 1770 | 1540 |
| 4700 | 472 | 12.5 × 35.5 | 0.028 | 0.056 | 2230 | 1890 | 18 × 20 | 0.032 | 0.064 | 1920 | 1720 |
| 5600 | 562 | 12.5 × 40 | 0.026 | 0.052 | 2460 | 2040 | 18 × 20 | 0.030 | 0.060 | 1980 | 1780 |
| 6800 | 682 | 16 × 31.5 | 0.024 | 0.048 | 2510 | 2130 | 18 × 25 | 0.027 | 0.054 | 2350 | 1980 |
| 8200 | 822 | 16 × 35.5 | 0.022 | 0.044 | 2770 | 2290 | 18 × 31.5 | 0.025 | 0.050 | 2390 | 2150 |
| 10000 | 103 | 16 × 40 | 0.020 | 0.040 | 3110 | 2470 | 18 × 31.5 | 0.023 | 0.046 | 2720 | 2240 |
| 12000 | 123 | 18 × 35.5 | 0.019 | 0.038 | 3050 | 2530 | | | | | |
| 15000 | 153 | 18 × 40 | 0.018 | 0.036 | 3300 | 2660 | | | | | |

| <div> <div>V(Code)</div> <div>Size code</div> <div>Item</div> <div>Cap.(μF)</div> <div>Code</div> </div> | | 10 (1A) | | | | | | | | | |
|--|-----|-----------------------------|--------------------|----------------|---------------------------|---------------|-----------------------------|--------------------|----------------|---------------------------|---------------|
| | | — | | | | | 6 | | | | |
| | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | |
| | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz |
| 68 | 680 | 5 × 11 | 0.80 | 1.60 | 155 | 97 | | | | | |
| 82 | 820 | 5 × 11 | 0.65 | 1.30 | 175 | 110 | | | | | |
| 100 | 101 | 6.3 × 11 | 0.55 | 1.10 | 210 | 135 | | | | | |
| 120 | 121 | 6.3 × 11 | 0.44 | 0.88 | 235 | 160 | | | | | |
| 150 | 151 | 6.3 × 11 | 0.35 | 0.70 | 265 | 185 | | | | | |
| 180 | 181 | 6.3 × 11 | 0.29 | 0.58 | 290 | 205 | | | | | |
| 220 | 221 | 6.3 × 15 | 0.24 | 0.48 | 370 | 270 | | | | | |
| 270 | 271 | 6.3 × 15 | 0.20 | 0.40 | 405 | 300 | | | | | |
| 330 | 331 | 8 × 11.5 | 0.16 | 0.32 | 460 | 350 | | | | | |
| 390 | 391 | 8 × 15 | 0.14 | 0.28 | 550 | 430 | 10 × 12.5 | 0.15 | 0.30 | 625 | 430 |
| 470 | 471 | 8 × 15 | 0.12 | 0.24 | 595 | 475 | 10 × 12.5 | 0.13 | 0.26 | 600 | 475 |
| 560 | 561 | 8 × 20 | 0.10 | 0.20 | 730 | 590 | 10 × 15 | 0.11 | 0.22 | 700 | 565 |
| 680 | 681 | 8 × 20 | 0.085 | 0.17 | 795 | 660 | 10 × 15 | 0.090 | 0.18 | 825 | 635 |
| 820 | 821 | 10 × 20 | 0.070 | 0.14 | 985 | 835 | 12.5 × 15 | 0.080 | 0.16 | 920 | 780 |
| 1000 | 102 | 10 × 20 | 0.060 | 0.12 | 1060 | 915 | 12.5 × 15 | 0.065 | 0.13 | 1040 | 895 |
| 1200 | 122 | 10 × 25 | 0.050 | 0.10 | 1260 | 1120 | 12.5 × 15 | 0.060 | 0.12 | 1060 | 930 |
| 1500 | 152 | 10 × 31.5 | 0.045 | 0.090 | 1450 | 1290 | 16 × 15 | 0.050 | 0.10 | 1330 | 1190 |
| 1800 | 182 | 12.5 × 20 | 0.039 | 0.078 | 1470 | 1320 | 16 × 15 | 0.044 | 0.088 | 1420 | 1270 |
| 2200 | 222 | 12.5 × 25 | 0.034 | 0.068 | 1710 | 1530 | 18 × 15 | 0.039 | 0.078 | 1600 | 1440 |
| 2700 | 272 | 12.5 × 31.5 | 0.030 | 0.060 | 1980 | 1740 | 16 × 20 | 0.035 | 0.070 | 1740 | 1560 |
| 3300 | 332 | 12.5 × 35.5 | 0.026 | 0.052 | 2230 | 1960 | 16 × 20 | 0.031 | 0.062 | 1850 | 1660 |
| 3900 | 392 | 12.5 × 40 | 0.024 | 0.048 | 2460 | 2120 | 18 × 20 | 0.028 | 0.056 | 2050 | 1840 |
| 4700 | 472 | 16 × 31.5 | 0.023 | 0.046 | 2420 | 2170 | 18 × 25 | 0.026 | 0.052 | 2350 | 2020 |
| 5600 | 562 | 16 × 35.5 | 0.021 | 0.042 | 2610 | 2340 | 18 × 25 | 0.024 | 0.048 | 2340 | 2100 |
| 6800 | 682 | 16 × 35.5 | 0.020 | 0.040 | 2770 | 2410 | 18 × 31.5 | 0.022 | 0.044 | 2720 | 2280 |
| 8200 | 822 | 16 × 40 | 0.019 | 0.038 | 3110 | 2530 | 18 × 35.5 | 0.021 | 0.042 | 3050 | 2420 |
| 10000 | 103 | 18 × 40 | 0.017 | 0.034 | 3300 | 2730 | | | | | |

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard ratings

| Cap.(μF) | | V(Code) Size Code Item Code | | 16 (1C) | | | | | | | | | |
|----------|-----|--------------------------------------|-------|------------------------------|--------------------|----------------|---------------------------|---------------|------------------------------|--------------------|----------------|---------------------------|---------------|
| | | | | — | | | | 6 | | | | | |
| | | | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | |
| | | | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 100kHz~ 200kHz | 105°C / 120Hz |
| 47 | 470 | 5 × 11 | 0.80 | 1.60 | 155 | 92 | | | | | | | |
| 56 | 560 | 5 × 11 | 0.65 | 1.30 | 175 | 105 | | | | | | | |
| 68 | 680 | 6.3 × 11 | 0.50 | 1.00 | 220 | 135 | | | | | | | |
| 82 | 820 | 6.3 × 11 | 0.42 | 0.84 | 240 | 155 | | | | | | | |
| 100 | 101 | 6.3 × 11 | 0.35 | 0.70 | 265 | 175 | | | | | | | |
| 120 | 121 | 6.3 × 11 | 0.29 | 0.58 | 290 | 195 | | | | | | | |
| 150 | 151 | 6.3 × 15 | 0.23 | 0.46 | 375 | 260 | | | | | | | |
| 180 | 181 | 6.3 × 15 | 0.20 | 0.40 | 405 | 285 | | | | | | | |
| 220 | 221 | 8 × 11.5 | 0.16 | 0.32 | 460 | 335 | | | | | | | |
| 270 | 271 | 8 × 15 | 0.14 | 0.28 | 550 | 410 | 10 × 12.5 | 0.14 | 0.28 | 625 | 430 | | |
| 330 | 331 | 8 × 15 | 0.12 | 0.24 | 595 | 455 | 10 × 12.5 | 0.12 | 0.24 | 625 | 480 | | |
| 390 | 391 | 8 × 20 | 0.10 | 0.20 | 730 | 570 | 10 × 15 | 0.10 | 0.20 | 730 | 570 | | |
| 470 | 471 | 8 × 20 | 0.090 | 0.18 | 770 | 615 | 10 × 15 | 0.090 | 0.18 | 825 | 615 | | |
| 560 | 561 | 10 × 20 | 0.075 | 0.15 | 950 | 770 | 12.5 × 15 | 0.080 | 0.16 | 920 | 745 | | |
| 680 | 681 | 10 × 20 | 0.065 | 0.13 | 1060 | 845 | 12.5 × 15 | 0.070 | 0.14 | 985 | 815 | | |
| 820 | 821 | 10 × 25 | 0.055 | 0.11 | 1260 | 1030 | 12.5 × 15 | 0.060 | 0.12 | 1060 | 895 | | |
| 1000 | 102 | 10 × 31.5 | 0.047 | 0.094 | 1410 | 1210 | 16 × 15 | 0.055 | 0.11 | 1270 | 1090 | | |
| 1200 | 122 | 12.5 × 20 | 0.041 | 0.082 | 1430 | 1250 | 16 × 15 | 0.046 | 0.092 | 1390 | 1220 | | |
| 1500 | 152 | 12.5 × 25 | 0.036 | 0.072 | 1700 | 1490 | 18 × 15 | 0.041 | 0.082 | 1560 | 1400 | | |
| 1800 | 182 | 12.5 × 31.5 | 0.032 | 0.064 | 1880 | 1690 | 16 × 20 | 0.037 | 0.074 | 1700 | 1530 | | |
| 2200 | 222 | 12.5 × 31.5 | 0.028 | 0.056 | 2010 | 1800 | 16 × 20 | 0.033 | 0.066 | 1800 | 1620 | | |
| 2700 | 272 | 12.5 × 35.5 | 0.025 | 0.050 | 2230 | 1990 | 16 × 25 | 0.030 | 0.060 | 2190 | 1800 | | |
| 3300 | 332 | 12.5 × 40 | 0.023 | 0.046 | 2460 | 2160 | 18 × 20 | 0.027 | 0.054 | 2090 | 1880 | | |
| 3900 | 392 | 16 × 31.5 | 0.022 | 0.044 | 2510 | 2220 | 18 × 25 | 0.025 | 0.050 | 2350 | 2060 | | |
| 4700 | 472 | 16 × 35.5 | 0.020 | 0.040 | 2680 | 2410 | 18 × 31.5 | 0.023 | 0.046 | 2720 | 2240 | | |
| 5600 | 562 | 16 × 40 | 0.019 | 0.038 | 3110 | 2530 | 18 × 35.5 | 0.022 | 0.044 | 2620 | 2350 | | |
| 6800 | 682 | 18 × 35.5 | 0.018 | 0.036 | 3050 | 2610 | | | | | | | |
| 8200 | 822 | 18 × 40 | 0.017 | 0.034 | 3300 | 2730 | | | | | | | |

| Cap.(μF) | | V(Code) Size Code Item Code | | 25 (1E) | | | | | | | | | |
|----------|-----|--------------------------------------|-------|------------------------------|--------------------|----------------|--|---------------|------------------------------|--------------------|----------------|--|---------------|
| | | | | — | | | | 6 | | | | | |
| | | | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mArms) | |
| | | | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / $\frac{10\text{kHz} \sim 200\text{kHz}}$ | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / $\frac{10\text{kHz} \sim 200\text{kHz}}$ | 105°C / 120Hz |
| 33 | 330 | 5 × 11 | 0.80 | 1.60 | 155 | 88 | | | | | | | |
| 39 | 390 | 5 × 11 | 0.65 | 1.30 | 175 | 100 | | | | | | | |
| 47 | 470 | 6.3 × 11 | 0.55 | 1.10 | 210 | 125 | | | | | | | |
| 56 | 560 | 6.3 × 11 | 0.44 | 0.88 | 235 | 140 | | | | | | | |
| 68 | 680 | 6.3 × 11 | 0.36 | 0.72 | 260 | 160 | | | | | | | |
| 82 | 820 | 6.3 × 11 | 0.30 | 0.60 | 285 | 180 | | | | | | | |
| 100 | 101 | 6.3 × 15 | 0.24 | 0.48 | 370 | 245 | | | | | | | |
| 120 | 121 | 6.3 × 15 | 0.20 | 0.40 | 405 | 275 | | | | | | | |
| 150 | 151 | 8 × 11.5 | 0.16 | 0.32 | 460 | 320 | | | | | | | |
| 180 | 181 | 8 × 15 | 0.14 | 0.28 | 550 | 390 | 10 × 12.5 | 0.15 | 0.30 | 625 | 395 | | |
| 220 | 221 | 8 × 15 | 0.11 | 0.22 | 625 | 455 | 10 × 12.5 | 0.13 | 0.26 | 600 | 435 | | |
| 270 | 271 | 8 × 20 | 0.095 | 0.19 | 750 | 560 | 10 × 15 | 0.11 | 0.22 | 700 | 525 | | |
| 330 | 331 | 8 × 20 | 0.085 | 0.17 | 795 | 610 | 10 × 15 | 0.095 | 0.19 | 825 | 575 | | |
| 390 | 391 | 10 × 20 | 0.070 | 0.14 | 985 | 770 | 12.5 × 15 | 0.080 | 0.16 | 920 | 720 | | |
| 470 | 471 | 10 × 20 | 0.065 | 0.13 | 1060 | 810 | 12.5 × 15 | 0.070 | 0.14 | 985 | 785 | | |
| 560 | 561 | 10 × 25 | 0.055 | 0.11 | 1260 | 990 | 12.5 × 15 | 0.060 | 0.12 | 1060 | 860 | | |
| 680 | 681 | 10 × 31.5 | 0.046 | 0.092 | 1420 | 1180 | 16 × 15 | 0.055 | 0.11 | 1270 | 1050 | | |
| 820 | 821 | 12.5 × 20 | 0.041 | 0.082 | 1440 | 1210 | 16 × 15 | 0.049 | 0.098 | 1340 | 1130 | | |
| 1000 | 102 | 12.5 × 25 | 0.036 | 0.072 | 1700 | 1430 | 18 × 15 | 0.043 | 0.086 | 1520 | 1310 | | |
| 1200 | 122 | 12.5 × 25 | 0.032 | 0.064 | 1760 | 1550 | 18 × 15 | 0.039 | 0.078 | 1600 | 1400 | | |
| 1500 | 152 | 12.5 × 31.5 | 0.029 | 0.058 | 1980 | 1780 | 16 × 20 | 0.034 | 0.068 | 1770 | 1590 | | |
| 1800 | 182 | 12.5 × 35.5 | 0.026 | 0.052 | 2230 | 1960 | 16 × 25 | 0.031 | 0.062 | 2190 | 1780 | | |
| 2200 | 222 | 12.5 × 40 | 0.024 | 0.048 | 2460 | 2120 | 18 × 20 | 0.028 | 0.056 | 2050 | 1840 | | |
| 2700 | 272 | 16 × 31.5 | 0.022 | 0.044 | 2510 | 2220 | 18 × 25 | 0.025 | 0.050 | 2350 | 2060 | | |
| 3300 | 332 | 16 × 35.5 | 0.020 | 0.040 | 2770 | 2410 | 18 × 31.5 | 0.023 | 0.046 | 2720 | 2240 | | |
| 3900 | 392 | 16 × 40 | 0.019 | 0.038 | 3110 | 2530 | 18 × 35.5 | 0.021 | 0.042 | 3050 | 2420 | | |
| 4700 | 472 | 18 × 40 | 0.018 | 0.036 | 3300 | 2660 | | | | | | | |

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

PM series

■ Standard ratings

| V(Code) Size code | | 35 (1V) | | | | | | | | | |
|----------------------|------|-------------------------------------|--------------------|----------------|--------------------------|---------------|-----------------------------|--------------------|----------------|--------------------------|---------------|
| | | — | | | | | 6 | | | | |
| | | Item Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | |
| | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz |
| Cap.(μF) | Code | | | | | | | | | | |
| 22 | 220 | 5 × 11 | 0.75 | 1.50 | 160 | 85 | | | | | |
| 27 | 270 | 5 × 11 | 0.60 | 1.20 | 180 | 99 | | | | | |
| 33 | 330 | 6.3 × 11 | 0.49 | 0.98 | 225 | 125 | | | | | |
| 39 | 390 | 6.3 × 11 | 0.41 | 0.82 | 245 | 140 | | | | | |
| 47 | 470 | 6.3 × 11 | 0.34 | 0.68 | 270 | 160 | | | | | |
| 56 | 560 | 6.3 × 11 | 0.28 | 0.56 | 295 | 180 | | | | | |
| 68 | 680 | 6.3 × 15 | 0.24 | 0.48 | 370 | 230 | | | | | |
| 82 | 820 | 6.3 × 15 | 0.19 | 0.38 | 415 | 265 | | | | | |
| 100 | 101 | 8 × 11.5 | 0.16 | 0.32 | 460 | 305 | | | | | |
| 120 | 121 | 8 × 15 | 0.14 | 0.28 | 550 | 370 | 10 × 12.5 | 0.15 | 0.30 | 625 | 375 |
| 150 | 151 | 8 × 15 | 0.12 | 0.24 | 595 | 415 | 10 × 12.5 | 0.12 | 0.24 | 625 | 435 |
| 180 | 181 | 8 × 20 | 0.10 | 0.20 | 730 | 520 | 10 × 15 | 0.11 | 0.22 | 700 | 500 |
| 220 | 221 | 8 × 20 | 0.085 | 0.17 | 795 | 580 | 10 × 15 | 0.090 | 0.18 | 825 | 560 |
| 270 | 271 | 10 × 20 | 0.070 | 0.14 | 985 | 735 | 12.5 × 15 | 0.080 | 0.16 | 920 | 690 |
| 330 | 331 | 10 × 20 | 0.060 | 0.12 | 1060 | 810 | 12.5 × 15 | 0.065 | 0.13 | 1020 | 780 |
| 390 | 391 | 10 × 25 | 0.055 | 0.11 | 1260 | 955 | 12.5 × 15 | 0.060 | 0.12 | 1060 | 825 |
| 470 | 471 | 10 × 31.5 | 0.046 | 0.092 | 1450 | 1130 | 16 × 15 | 0.055 | 0.11 | 1270 | 1010 |
| 560 | 561 | 12.5 × 20 | 0.041 | 0.082 | 1430 | 1160 | 16 × 15 | 0.048 | 0.096 | 1360 | 1100 |
| 680 | 681 | 12.5 × 25 | 0.036 | 0.072 | 1700 | 1370 | 18 × 15 | 0.042 | 0.084 | 1540 | 1270 |
| 820 | 821 | 12.5 × 25 | 0.032 | 0.064 | 1760 | 1490 | 18 × 15 | 0.038 | 0.076 | 1620 | 1370 |
| 1000 | 102 | 12.5 × 31.5 | 0.029 | 0.058 | 1980 | 1710 | 16 × 20 | 0.034 | 0.068 | 1770 | 1530 |
| 1200 | 122 | 12.5 × 35.5 | 0.026 | 0.052 | 2230 | 1920 | 16 × 25 | 0.031 | 0.062 | 2190 | 1740 |
| 1500 | 152 | 12.5 × 40 | 0.024 | 0.048 | 2460 | 2120 | 18 × 20 | 0.028 | 0.056 | 2050 | 1840 |
| 1800 | 182 | 16 × 31.5 | 0.022 | 0.044 | 2510 | 2220 | 18 × 25 | 0.025 | 0.050 | 2350 | 2060 |
| 2200 | 222 | 16 × 35.5 | 0.020 | 0.040 | 2770 | 2410 | 18 × 31.5 | 0.023 | 0.046 | 2720 | 2240 |
| 2700 | 272 | 16 × 40 | 0.018 | 0.036 | 3110 | 2610 | 18 × 35.5 | 0.021 | 0.042 | 3050 | 2420 |
| 3300 | 332 | 18 × 40 | 0.017 | 0.034 | 3300 | 2730 | | | | | |

| V(Code) Size code | | 50 (1H) | | | | | | | | | |
|----------------------|------|-------------------------------------|--------------------|----------------|--------------------------|---------------|-----------------------------|--------------------|----------------|--------------------------|---------------|
| | | — | | | | | 6 | | | | |
| | | Item Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | |
| | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz |
| Cap.(μF) | Code | | | | | | | | | | |
| 0.47 | R47 | 5 × 11 | 23.0 | 46.0 | 22 | 11 | | | | | |
| 0.68 | R68 | 5 × 11 | 16.0 | 32.0 | 28 | 14 | | | | | |
| 1 | 010 | 5 × 11 | 11.0 | 22.0 | 36 | 18 | | | | | |
| 1.5 | 1R5 | 5 × 11 | 7.50 | 15.0 | 45 | 22 | | | | | |
| 2.2 | 2R2 | 5 × 11 | 5.00 | 10.0 | 54 | 27 | | | | | |
| 3.3 | 3R3 | 5 × 11 | 3.30 | 6.60 | 66 | 33 | | | | | |
| 4.7 | 4R7 | 5 × 11 | 2.20 | 4.40 | 81 | 40 | | | | | |
| 6.8 | 6R8 | 5 × 11 | 1.80 | 3.60 | 91 | 45 | | | | | |
| 10 | 100 | 5 × 11 | 1.40 | 2.80 | 115 | 57 | | | | | |
| 12 | 120 | 5 × 11 | 1.20 | 2.40 | 125 | 62 | | | | | |
| 15 | 150 | 5 × 11 | 0.93 | 1.86 | 145 | 72 | | | | | |
| 18 | 180 | 5 × 11 | 0.80 | 1.60 | 165 | 79 | | | | | |
| 22 | 220 | 6.3 × 11 | 0.65 | 1.30 | 195 | 100 | | | | | |
| 27 | 270 | 6.3 × 11 | 0.53 | 1.06 | 215 | 115 | | | | | |
| 33 | 330 | 6.3 × 11 | 0.43 | 0.86 | 240 | 135 | | | | | |
| 39 | 390 | 6.3 × 11 | 0.36 | 0.72 | 260 | 150 | | | | | |
| 47 | 470 | 6.3 × 15 | 0.30 | 0.60 | 330 | 195 | | | | | |
| 56 | 560 | 6.3 × 15 | 0.25 | 0.50 | 360 | 220 | | | | | |
| 68 | 680 | 8 × 11.5 | 0.20 | 0.40 | 415 | 255 | | | | | |
| 82 | 820 | 8 × 15 | 0.17 | 0.34 | 505 | 320 | 10 × 12.5 | 0.18 | 0.36 | 510 | 330 |
| 100 | 101 | 8 × 20 | 0.14 | 0.28 | 620 | 410 | 10 × 15 | 0.16 | 0.32 | 580 | 385 |
| 120 | 121 | 8 × 20 | 0.12 | 0.24 | 755 | 455 | 10 × 15 | 0.13 | 0.26 | 755 | 435 |
| 150 | 151 | 10 × 20 | 0.10 | 0.20 | 820 | 570 | 12.5 × 15 | 0.11 | 0.22 | 785 | 545 |
| 180 | 181 | 10 × 20 | 0.085 | 0.17 | 945 | 635 | 12.5 × 15 | 0.095 | 0.19 | 845 | 605 |
| 220 | 221 | 10 × 25 | 0.075 | 0.15 | 1150 | 760 | 12.5 × 15 | 0.080 | 0.16 | 920 | 670 |
| 270 | 271 | 10 × 31.5 | 0.065 | 0.13 | 1200 | 900 | 16 × 15 | 0.070 | 0.14 | 1120 | 840 |
| 330 | 331 | 10 × 31.5 | 0.055 | 0.11 | 1300 | 995 | 16 × 15 | 0.060 | 0.12 | 1210 | 925 |
| 390 | 391 | 12.5 × 25 | 0.048 | 0.096 | 1440 | 1120 | 16 × 15 | 0.055 | 0.11 | 1270 | 990 |
| 470 | 471 | 12.5 × 25 | 0.044 | 0.088 | 1500 | 1190 | 18 × 15 | 0.046 | 0.092 | 1470 | 1170 |
| 560 | 561 | 12.5 × 31.5 | 0.040 | 0.080 | 1720 | 1360 | 16 × 20 | 0.044 | 0.088 | 1550 | 1260 |
| 680 | 681 | 12.5 × 35.5 | 0.036 | 0.072 | 1890 | 1530 | 16 × 20 | 0.040 | 0.080 | 1630 | 1350 |
| 820 | 821 | 12.5 × 40 | 0.033 | 0.066 | 2120 | 1700 | 18 × 20 | 0.036 | 0.072 | 1810 | 1530 |
| 1000 | 102 | 16 × 31.5 | 0.030 | 0.060 | 2120 | 1830 | 18 × 25 | 0.033 | 0.066 | 2020 | 1730 |
| 1200 | 122 | 16 × 35.5 | 0.028 | 0.056 | 2320 | 1990 | 18 × 31.5 | 0.031 | 0.062 | 2140 | 1880 |
| 1500 | 152 | 16 × 40 | 0.026 | 0.052 | 2650 | 2170 | 18 × 31.5 | 0.029 | 0.058 | 2340 | 1990 |
| 1800 | 182 | 18 × 35.5 | 0.025 | 0.050 | 2620 | 2210 | | | | | |
| 2200 | 222 | 18 × 40 | 0.024 | 0.048 | 2790 | 2300 | | | | | |

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard ratings

| Cap. (μF) | | V(Code) | | 63 (1J) | | | | | | | |
|-----------|-----|------------------------------|--------------------|----------------|--------------------------|---------------|------------------------------|--------------------|----------------|--------------------------|---------------|
| | | Size code | | — | | | | 6 | | | |
| | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | | Case size φ D × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mA rms) | |
| | | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | −10°C / 100kHz | 105°C / 10kHz~ 200kHz | 105°C / 120Hz |
| 10 | 100 | 5 × 11 | 1.06 | 2.12 | 135 | 67 | | | | | |
| 12 | 120 | 5 × 11 | 0.93 | 1.86 | 145 | 72 | | | | | |
| 15 | 150 | 6.3 × 11 | 0.73 | 1.46 | 185 | 92 | | | | | |
| 18 | 180 | 6.3 × 11 | 0.63 | 1.26 | 195 | 100 | | | | | |
| 22 | 220 | 6.3 × 11 | 0.52 | 1.04 | 215 | 110 | | | | | |
| 27 | 270 | 6.3 × 11 | 0.43 | 0.86 | 240 | 130 | | | | | |
| 33 | 330 | 6.3 × 15 | 0.35 | 0.70 | 305 | 170 | | | | | |
| 39 | 390 | 6.3 × 15 | 0.30 | 0.60 | 330 | 190 | | | | | |
| 47 | 470 | 8 × 11.5 | 0.25 | 0.50 | 365 | 215 | | | | | |
| 56 | 560 | 8 × 15 | 0.21 | 0.42 | 450 | 275 | 10 × 12.5 | 0.23 | 0.46 | 450 | 275 |
| 68 | 680 | 8 × 15 | 0.17 | 0.34 | 500 | 315 | 10 × 12.5 | 0.19 | 0.38 | 495 | 310 |
| 82 | 820 | 8 × 20 | 0.15 | 0.30 | 600 | 385 | 10 × 15 | 0.16 | 0.32 | 580 | 375 |
| 100 | 101 | 10 × 20 | 0.12 | 0.24 | 750 | 495 | 12.5 × 15 | 0.14 | 0.28 | 695 | 460 |
| 120 | 121 | 10 × 20 | 0.10 | 0.20 | 820 | 555 | 12.5 × 15 | 0.12 | 0.24 | 750 | 510 |
| 150 | 151 | 10 × 25 | 0.090 | 0.18 | 950 | 665 | 12.5 × 15 | 0.095 | 0.19 | 845 | 590 |
| 180 | 181 | 10 × 31.5 | 0.075 | 0.15 | 1110 | 790 | 16 × 15 | 0.080 | 0.16 | 1050 | 750 |
| 220 | 221 | 12.5 × 20 | 0.065 | 0.13 | 1140 | 835 | 16 × 15 | 0.070 | 0.14 | 1120 | 820 |
| 270 | 271 | 12.5 × 25 | 0.055 | 0.11 | 1340 | 1000 | 18 × 15 | 0.060 | 0.12 | 1290 | 965 |
| 330 | 331 | 12.5 × 25 | 0.049 | 0.098 | 1420 | 1090 | 18 × 15 | 0.050 | 0.10 | 1410 | 1080 |
| 390 | 391 | 12.5 × 31.5 | 0.043 | 0.086 | 1620 | 1260 | 16 × 20 | 0.047 | 0.094 | 1500 | 1170 |
| 470 | 471 | 12.5 × 35.5 | 0.039 | 0.078 | 1780 | 1420 | 16 × 25 | 0.042 | 0.084 | 1700 | 1350 |
| 560 | 561 | 12.5 × 40 | 0.035 | 0.070 | 1950 | 1580 | 18 × 20 | 0.039 | 0.078 | 1730 | 1400 |
| 680 | 681 | 16 × 31.5 | 0.032 | 0.064 | 2050 | 1700 | 18 × 25 | 0.035 | 0.070 | 1940 | 1610 |
| 820 | 821 | 16 × 35.5 | 0.029 | 0.058 | 2220 | 1880 | 18 × 31.5 | 0.032 | 0.064 | 2110 | 1780 |
| 1000 | 102 | 16 × 40 | 0.027 | 0.054 | 2370 | 2050 | 18 × 35.5 | 0.029 | 0.058 | 2280 | 1970 |
| 1200 | 122 | 18 × 40 | 0.025 | 0.050 | 2510 | 2210 | | | | | |

■ Standard ratings

| Cap.(μF) | V(Code) | Size code | Item | 100 (2A) | | | | | | | | | |
|----------|---------|-----------|-------------|-----------------------------|--------------------|----------------|------------------------|---------------|-----------------------------|--------------------|----------------|------------------------|---------------|
| | | | | — | | | | 6 | | | | | |
| | | | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mAmps) | | Case size φD × L (mm) | Impedance (Ω) MAX. | | Rated ripple (mAmps) | |
| | | | | | 20°C / 100kHz | -10°C / 100kHz | 105°C / 10kHz ~ 200kHz | 105°C / 120Hz | | 20°C / 100kHz | -10°C / 100kHz | 105°C / 10kHz ~ 200kHz | 105°C / 120Hz |
| 0.47 | R47 | | 5 × 11 | | 43.0 | 116.0 | 17 | 8 | | | | | |
| 0.68 | R68 | | 5 × 11 | | 23.0 | 62.0 | 23 | 11 | | | | | |
| 1 | 010 | | 5 × 11 | | 17.0 | 46.0 | 27 | 13 | | | | | |
| 1.5 | 1R5 | | 5 × 11 | | 10.0 | 27.0 | 35 | 17 | | | | | |
| 2.2 | 2R2 | | 5 × 11 | | 6.60 | 18.0 | 43 | 21 | | | | | |
| 3.3 | 3R3 | | 5 × 11 | | 4.10 | 11.0 | 54 | 27 | | | | | |
| 4.7 | 4R7 | | 6.3 × 11 | | 2.80 | 7.60 | 68 | 34 | | | | | |
| 6.8 | 6R8 | | 6.3 × 11 | | 1.90 | 5.10 | 83 | 41 | | | | | |
| 10 | 100 | | 6.3 × 11 | | 1.20 | 3.20 | 104 | 52 | | | | | |
| 12 | 120 | | 6.3 × 11 | | 1.00 | 2.70 | 150 | 57 | | | | | |
| 15 | 150 | | 6.3 × 15 | | 0.81 | 2.20 | 131 | 65 | | | | | |
| 18 | 180 | | 6.3 × 15 | | 0.67 | 1.80 | 220 | 73 | | | | | |
| 22 | 220 | | 8 × 11.5 | | 0.55 | 1.50 | 275 | 122 | | | | | |
| 27 | 270 | | 8 × 15 | | 0.47 | 1.30 | 269 | 146 | 10 × 12.5 | 0.50 | 1.40 | 380 | 145 |
| 33 | 330 | | 8 × 15 | | 0.38 | 1.00 | 360 | 169 | 10 × 12.5 | 0.42 | 1.10 | 293 | 166 |
| 39 | 390 | | 8 × 20 | | 0.33 | 0.89 | 490 | 202 | 10 × 15 | 0.36 | 0.97 | 337 | 193 |
| 47 | 470 | | 10 × 20 | | 0.28 | 0.76 | 423 | 252 | 12.5 × 15 | 0.31 | 0.84 | 402 | 239 |
| 56 | 560 | | 10 × 20 | | 0.24 | 0.65 | 620 | 274 | 12.5 × 15 | 0.27 | 0.73 | 430 | 258 |
| 68 | 680 | | 10 × 25 | | 0.21 | 0.57 | 795 | 326 | 12.5 × 15 | 0.23 | 0.62 | 466 | 289 |
| 82 | 820 | | 10 × 31.5 | | 0.18 | 0.49 | 606 | 386 | 16 × 15 | 0.19 | 0.51 | 681 | 433 |
| 100 | 101 | | 10 × 31.5 | | 0.15 | 0.41 | 955 | 438 | 16 × 15 | 0.17 | 0.46 | 719 | 475 |
| 120 | 121 | | 12.5 × 25 | | 0.13 | 0.35 | 1040 | 519 | 16 × 15 | 0.14 | 0.38 | 793 | 531 |
| 150 | 151 | | 12.5 × 25 | | 0.11 | 0.30 | 798 | 553 | 18 × 15 | 0.12 | 0.32 | 917 | 635 |
| 180 | 181 | | 12.5 × 31.5 | | 0.098 | 0.26 | 1270 | 641 | 16 × 20 | 0.11 | 0.30 | 1240 | 706 |
| 220 | 221 | | 12.5 × 35.5 | | 0.087 | 0.23 | 1450 | 730 | 16 × 25 | 0.093 | 0.25 | 1440 | 854 |
| 270 | 271 | | 12.5 × 40 | | 0.072 | 0.19 | 1610 | 843 | 18 × 20 | 0.080 | 0.22 | 1450 | 918 |
| 330 | 331 | | 16 × 31.5 | | 0.062 | 0.17 | 1790 | 1160 | 18 × 25 | 0.070 | 0.19 | 1650 | 1080 |
| 390 | 391 | | 16 × 35.5 | | 0.053 | 0.14 | 2000 | 1340 | 18 × 31.5 | 0.062 | 0.17 | 1850 | 1240 |
| 470 | 471 | | 16 × 40 | | 0.047 | 0.13 | 2200 | 1530 | 18 × 35.5 | 0.056 | 0.15 | 1970 | 1410 |
| 560 | 561 | | 18 × 35.5 | | 0.041 | 0.11 | 2250 | 1680 | | | | | |
| 680 | 681 | | 18 × 40 | | 0.036 | 0.097 | 2300 | 1910 | | | | | |

※ In case of low profile type, ⑥ will be put at 12th digit of type numbering system.

| Cap.(μF) | V(Code) | Code | 160 | | 200 | | 250 | | 315 | | 350 | | 400 | | 450 | |
|----------|---------|------|-----------|-----|-----------|-----|-----------|-----|-----------|-----|-----------|-----|-----------|-----|--------------------------|-----|
| | | | 2C | | 2D | | 2E | | 2F | | 2V | | 2G | | 2W | |
| 1 | 010 | | 8 × 11.5 | 19 | 8 × 11.5 | 19 | 8 × 11.5 | 19 | 8 × 11.5 | 19 | 10 × 12.5 | 21 | 10 × 12.5 | 17 | 10 × 15 | 17 |
| 2.2 | 2R2 | | 8 × 11.5 | 30 | 8 × 11.5 | 30 | 10 × 12.5 | 32 | 10 × 12.5 | 32 | 10 × 15 | 34 | 10 × 15 | 28 | 10 × 20 | 28 |
| 3.3 | 3R3 | | 10 × 12.5 | 50 | 10 × 12.5 | 50 | 10 × 15 | 52 | 10 × 15 | 52 | 10 × 20 | 54 | 10 × 20 | 47 | 12.5 × 20 | 48 |
| 4.7 | 4R7 | | 10 × 12.5 | 57 | 10 × 15 | 60 | 10 × 15 | 60 | 10 × 20 | 65 | 10 × 20 | 65 | 12.5 × 20 | 55 | 12.5 × 25 | 55 |
| 10 | 100 | | 10 × 15 | 90 | 10 × 20 | 95 | 12.5 × 20 | 98 | 12.5 × 20 | 98 | 12.5 × 25 | 100 | 12.5 × 25 | 85 | 16 × 25 | 90 |
| 22 | 220 | | 12.5 × 20 | 140 | 12.5 × 25 | 145 | 16 × 25 | 150 | 16 × 25 | 150 | 16 × 25 | 150 | 16 × 31.5 | 130 | 16 × 35.5 | 135 |
| 33 | 330 | | 12.5 × 25 | 175 | 16 × 25 | 180 | 16 × 25 | 180 | 16 × 31.5 | 185 | 16 × 35.5 | 190 | 18 × 35.5 | 170 | 18 × 40 | 170 |
| 47 | 470 | | 16 × 25 | 220 | 16 × 25 | 220 | 16 × 31.5 | 225 | 18 × 35.5 | 235 | 18 × 40 | 240 | | | Case size φD × L (mm) | ※ |
| 100 | 101 | | 16 × 35.5 | 330 | 18 × 40 | 345 | 18 × 40 | 345 | | | | | | | | |

※ Rated Ripple (mAmps) at 105°C 120Hz