



'10 - 2

Small size / Low profile / Super low ESR / High capacitance

** Endurance : 105C x RV x 2,000h

** Damp heat : 60deg.C x 90% RHx 1,000h (No voltage)

Introducing additional models (highlighted in red)

SEPC Series Characteristics List

Size code	Part Number	Rated Voltage (V)	Rated Capacitance (uF)	ESR(mOHM)(max.) 100kHz to 300kHz/20C	Rated ripple current 100kHz (mA)rms at105C	Tangent of loss angle (% max.)	Leakage current (uA) (max.) After 2 minutes
B9	2SEPC100MZ	2.5	100	7	4180	10	500
	2SEPC330MZ	2.5	330	7	4180	10	500
	2SEPC470MZ	2.5	470	7	4180	10	500
	2SEPC560MZ	2.5	560	7	4180	10	500
C55	6SEPC220M	6.3	220	18	2980	12	280
C6	16SEPC100M	16	100	24	2490	10	320
	2SEPC390M	2.5	390	10	3900	12	500
C9	16SEPC100MW	16	100	10	4680	10	500
	6SEPC470MW	6.3	470	7	5600	10	592
	6SEPC560MW	6.3	560	7	5600	10	705
	4SEPC560MW	4	560	7	5600	10	500
	2SEPC330MW	2.5	330	7	5600	10	500
	2SEPC560MW	2.5	560	7	5600	10	500
	2SEPC820MW	2.5	820	7	5600	10	500
E7	16SEPC150MD	16	150	22	3220	12	500
	16SEPC220MD	16	220	13	4150	10	500
	10SEPC270MD	10	270	22	3220	12	500
	2SEPC820MD	2.5	820	8	5300	10	500
E9	16SEPC180MX	16	180	10	5000	10	576
	16SEPC270MX	16	270	10	5000	10	864
	6SEPC470MX	6.3	470	8	5700	10	592
	6SEPC560MX	6.3	560	7	6100	10	705
	4SEPC560MX	4	560	7	6100	10	500
	2SEPC560MX	2.5	560	8	4700	10	280
	2SEPC820MX	2.5	820	7	6100	10	500
	2SEPC820MY	2.5	820	5	7200	10	500
E12	16SEPC180M	16	180	16	4360	10	576
	16SEPC270M	16	270	11	5000	10	864
E13	6SEPC470M	6.3	470	8	5700	10	592
	4SEPC560M	4	560	7	6100	10	500
	4SEPC680M	4	680	7	6100	10	544
	2R5SEPC820M	2.5	820	7	6100	10	500
F13	16SEPC470M	16	470	10	6100	10	1504
	6SEPC680M	6.3	680	7	6640	10	857
	6SEPC1500M	6.3	1500	10	5560	10	1890
	4SEPC820M	4	820	7	6640	10	656
	2SEPC2700M	2.5	2700	10	5560	10	1350

Dimensions

(unit:mm)

Size code	pi D+0.5max.	Lmax.	F	pi d+/-0.05
B9	5.0	9.0	2.0+/-0.5	0.6
C55	6.3	5.5	2.5+/-0.5	0.45
C6	6.3	6.0	2.5+/-0.5	0.45*1
C9	6.3	9.0	2.5+/-0.5	0.6
E7	8.0	7.0	3.5+/-0.5	0.45*2
E9	8.0	9.0	3.5+/-0.5	0.6
E12	8.0	12.0	3.5+/-0.5	0.6
E13	8.0	13.0	3.5+/-0.5	0.6
F13	10.0	13.0	5.0+/-0.5	0.6

*B9,C55,C6,C9,E7,E9 size flat rubber is used.

*1 2SEPC390M : 0.5+/-0.05

*2 2SEPC820MD : 0.6+/-0.05


Size List

RV:rated voltage (SV):surge voltage (room temperature)


RV (SV)	2.5 (3.3)	4 (5.2)	6.3 (8.2)	10 (12)	16 (18)
uF					
100	B9				C6,C9
150					E7
180					E9,E12
220			C55		E7
270				E7	E9,E12
330	B9,C9				
390	C6				
470	B9		C9,E9,E13		F13
560	B9,C9,E9	C9,E9,E13	C9,E9		
680		E13	F13		
820	C9,E7,E9,E13	F13			
1000	E9				
1500			F13		
2700	F13				

Form figure

E12,E13,F13size



B9,C55,C6,C9,E7,E9size



This flier is a supplement of SANYO Capacitors General Catalog. Please confirm the specifications in the catalog, before using an OS-CON.